



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® RapidFuse® Super Glue Gel Adhesive

PRODUCT DESCRIPTION

DAP® RapidFuse® Super Glue Gel bonds virtually all materials with a professional strength, durable weatherproof bond. This easy to use, no drip gel formula can be repositioned within 3 minutes with no adhesion loss, unlike traditional super glues. RapidFuse® provides a clear bond with no dripping glue or mess that sets in 30 seconds and cures in four hours for interior and exterior use.



PACKAGING	COLOR	UPC
0.7 oz (20 g) Tube	Clear	7079800178
0.13 oz (4 g) Control Applicator	Clear	7079800179

SUGGESTED USES

- Wood
- Aluminum
- Steel
- Rubber
- ABS
- PVC
- Melamine/Laminate HPL
- Polycarbonate
- Ceramics & Porcelain
- Glass
- Fabric
- Stone & Concrete
- Tile
- Paper
- Composites



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

APPLICATION

INSTRUCTIONS: READ DIRECTIONS AND SAFETY INFORMATION BEFORE USE!

RapidFuse® Super Glue Gel 7079800178

1. Surfaces should be clean and dry before bonding.
2. Screw cap and nozzle assembly onto adhesive tube until completely tightened.
3. Unscrew cap and squeeze a small amount of glue to one surface.
4. Press the two surfaces together for 10 to 30 seconds.
5. Replace cap and store in a cool, dry place.

RapidFuse® Super Glue Gel 7079800179

1. Surfaces should be clean and dry before bonding.
2. Screw cap and nozzle assembly onto control applicator until completely tightened.
3. Unscrew cap and apply slight pressure to sides of applicator.
4. Apply a small amount of glue to one surface.
5. Press the two surfaces together for 10 to 30 seconds.
6. Replace cap and store in a cool, dry place.

Note:

Not suitable for polyethylene, polypropylene or PTFE. Pretest for glass projects. Bonded items should not be placed in oven, microwave, or dishwasher.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Adhesive Base:	Ethyl Cyanoacrylate
Consistency:	Gel
Volatile:	>2%
Non-Volatiles:	98%
Viscosity:	90,000 – 120,000 cps
Flash Point:	190.4 F (88 C)
Weight/Gallon:	8.85 lbs/gal
Odor:	Sharp
Application Temperature Range:	40°F to 105°F
Optimum Bottle Temperature:	55°F to 85°F
Service Temperature Range:	0°F to 120°F
Handling Time:	5 Minutes
Full Cure:	4 Hours
Freeze/Thaw Stability:	Stable
Coverage:	5-15 mL/sq. ft. (Optimal coverage is based on substrate evenness and porosity)
Appearance:	Clear Gel
Shelf Life:	18 Months Minimum @ 70°F

CLEAN UP & STORAGE

Do not transfer to any other container. Keep container tightly closed. If nozzle clogs, clear with a pin.

Prior to cure: Clean excess adhesive with dry paper towel. After cleaning, wet any paper towel used for wiping off glue with water before disposal.

Hands: Soak in warm soapy water and gently peel off roll adhesive off (DO NOT PULL), flush contact area with water and seek medical attention if needed.

After cure: Cured adhesive must be cut or scraped away or removed with acetone. Do not use acetone or any other solvent to clean skin.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

SAFETY

WARNING! EYE IRRITANT. BONDS SKIN INSTANTLY. Contains ethyl cyanoacrylate. Avoid contact with skin, eyes and clothing. Avoid prolonged breathing of vapors. Use with adequate ventilation. **KEEPOUT OF THE REACH OF CHILDREN.** **FIRST AID:** Skin Contact – Soak in warm soapy water and gently peel or roll adhesive off (**DO NOT PULL**). If spilled on clothing, remove and rinse with cold water. Eye Contact – Flush with water for at least 15 minutes; contact physician. Ingestion – do not induce vomiting. If lips are bonded together, use warm water to gently separate. Contact physician. Inhalation – Remove to fresh air; contact physician.

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.com or by calling **888-DAP-TIPS**.

WARRANTY

WARRANTY: DAP will provide replacement product or refund sales price if product fails to perform when used as directed within one year of the purchase date. Call 888-DAP-TIPS, with your sales receipt and product container available, to arrange for warranty fulfillment. DAP is not liable for incidental or consequential damages.

COMPANY IDENTIFICATION

Manufacturer: DAP Global Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call 888-DAP-TIPS or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com